

## OWT-Ultracoat® B

### Acrylic Polyurethane Binder

- 2K PU modified binder
- Superior clarity
- High performance binder
- Easily dispersible

Rev. No. 02/2015

### DESCRIPTION

OWT Ultracoat® B is a high performance acrylic polyurethane 2K binder for all kind of substrate. Use for binder application for, help protect surface from oxygen and other contamination and also improve adhesion between each layer of coating film.

### PROPERTIES

Chemical	: Acrylic Polyurethane Modified
pH (10% solution)	: 9
Appearance	: Amber translucent liquid
Ionic charge	: Nonionic

### APPLICATION & DOSAGE

OWT Ultracoat® B can use for wide range coating and adhesive application design for all kind of substrate such as metal, alloy, aluminum, wood and plastic. The substrate must be dry and no dust before apply the Ultracoat® B.

**PACKAGING**

1 Kg / Bottle, 4 Kg / Bottle

**PRICE**

Contact to sales representative

The information contained in this Technical Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information provided herein is based on technical data that Organic Wealth (Thailand) Co., Ltd believes to be reliable, however we make no representation or warranty as to the completeness or accuracy thereof and we assume no liability resulting from its use or for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgment as to the appropriateness of its use, and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.