

OWT-Antifoam ® 744

Antifoam

- Specially for coating applications
- Effective at low concentrations
- Enhances general wet end foam management
- Effective in different surfactant stabilized foam systems
- Re-Creation of foam will be avoided

Rev. No. 02/2015

DESCRIPTION

OWT Antifoam ® 744 for Water treatment is an effective antifoaming agent designed for Water treatment application. It shows excellent performance in the control of foams in system by significantly reducing the entrained air content.

SPECIFICATIONS

PHYSICAL PROPERTY

Chemical	: Modified Silicone
Appearance	: Light Amber liquid
Active Content	: 100 %
Solubility	: Miscible with chloroform, hydrocarbon
Viscosity	: 200-500 cps
(Bookfield Spindle No3, 12RPM)	

APPLICATION & DOSAGE

OWT Antifoam ® 744 is used at concentration levels ranging 0.2 to 0.5% on total batch weight. Optimum levels for specific formulation should be determined by laboratory evaluation.

PACKAGING

25 Kgs / Pail
200 Kgs / Drum
1,000 Kgs / IBC

PRICE

Contact to sales representative

The information contained in this Technical Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information provided herein is based on technical data that Organic Wealth (Thailand) Co., Ltd believes to be reliable, however we make no representation or warranty as to the completeness or accuracy thereof and we assume no liability resulting from its use or for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgment as to the appropriateness of its use, and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.